



PDS-100G-GN/ID Spectrometric Personal Radiation Detector

The PDS-100G/ID and PDS-100GN/ID are the most ultimate evolution of the gamma and gamma/neutron radiation detectors offering embedded spectrum acquisition and identification.

These sensitive pocket-sized devices are designed to detect, locate, quantify and identify radioactive sources to discriminate on the spot Naturally Occurring Radioactive Material (NORM) and medical isotopes against industrial sources or Special Nuclear Materials.

High sensitivity provides better spectra in a shorter time. Fully automated acquisition and identification as well as manual modes are provided.

Identification results are displayed as a list of isotopes with categories and confidence levels. Spectra and ID results are memorized for later transmission.

PDS-100G/ID and PDS-100GN/ID have been designed specially for First Responders, Law Enforcement, Customs inspectors and for Personnel and Site security in critical infrastructures.

FEATURES

Detection, Search and Identification of nuclear material for Homeland Security applications.

- Small, rugged, compact, user-friendly
- High sensitivity and fast response time
- Embedded identification, automated & manual mode
- Visual, audio and vibration alarms
- Wireless communication interface

VERSIONS:

- PDS-100G/ID: Gamma version
- PDS-100GN/ID: Gamma and Neutron version

health physics

A Mirion Technologies Division

Featuring:



DETECTION

- Detector gamma CsI(Tl): ≥ 400 cps per $\mu\text{Sv/h}$ for ^{137}Cs
- Detector neutron LiI(Eu) (GN version only)
- Gamma dose rate display 0.01 $\mu\text{Sv/h}$ to 100 $\mu\text{Sv/h}$ (1 $\mu\text{rem/h}$ to 10 mrem/h)
- Gamma count rate display: 0 to 99 999 cps
- Neutron count rate display: 0.0 to 999 cps
- Gamma alarm response time:
- Standard threshold: 0.5 $\mu\text{Sv/h}$ step, alarm within 1 s
- Sensitive threshold: 0.05 $\mu\text{Sv/h}$ step, alarm within 3 s
- Neutron alert response time: mean time to detect 20000 n/s Cf252 at 10 cm: ≤ 2 sec.

SEARCH

- 1s integration time with chirp

SPECTROMETRY AND IDENTIFICATION

- 512 / 1024 channels spectra : 30keV to 1.7 MeV
- Automated alarm triggered mode with auto confirmation
- Manual mode with preset time and/or counts and resume capability
- Identification by NMD algorithm
 - up to 4 isotopes mixed
 - detectability grade, unknown or ID unsure indication
 - identification time at 1 $\mu\text{Sv/h}$ typical 1 minute
 - designed to exceed ANSI N42-48 SPRD standard

| | |
|-------------------|---|
| NORM | 40K, 226Ra and daughters, 232Th and daughters |
| Medical | 18F, 51Cr, 67Ga , 75Se, 99mTc , 111In, 123I, 131I, 201Tl |
| Industrial | 22Na, 57Co, 60Co, 133Ba, 137Cs, 152Eu, 192Ir, 241Am |
| SNM | 235U, 238U, 239Pu |

In **bold**, isotopes addressed by ANSI for SPRD

FUNCTIONAL FEATURES

- Detection, search and/or identification mode
- Source indication alarm and danger alarm
- Visual, audible and silent alarms (vibration, earphone)

- Easy-to-read display (OLED technology)
- Memory of 100/50 512 ch/1024 ch. spectra and >1000 events
- IRDA and Bluetooth® technology communication

ELECTRICAL & MECHANICAL CHARACTERISTICS

- Power supply: 2 x AA batteries (Lithium, Alkaline or Ni-MH); lifetime typical 100 hours
- Dimensions (l x w x h): 123 x 74 x 43 mm (4.84 x 2.91 x 1.69 in); weight: 300 g (10.58 oz)

ENVIRONMENTAL CHARACTERISTICS

- Temperature range:- 20°C to 50°C (-4°F to 122°F)
ID: -15°C to +45°C (5°F to 115°F)
- EMI, shock, vibration, drop and water resistant

ACCESSORIES

- PDSmass software for remote display, spectra and historic retrieve, parameters settings
- SMI software for spectra analysis and identification replay
- Silicon protection
- Belt Clip
- Pouch with belt clip
- External power supply / battery charger




Detection mode screen




Manual ID in progress



Search mode screen



NMD result screen



Auto ID in progress



Spectra view with PDSmass



MIRION Health Physics
 TECHNOLOGIES Division

Mirion Technologies (MGPI) Inc
 5000 Highlands Parkway
 Suite 150
 Smyrna Georgia 30082
 USA
 T +1.770.432.2744
 F +1.770.432.9179

Mirion Technologies (MGPI) SA
 BP 1
 F-13113 Lamanon
 France
 T +33 (0) 4 90 59 59 59
 F +33 (0) 4 90 59 55 18

Mirion Technologies (RADOS) Oy
 P.O. Box 506
 FIN-20101 Turku
 Finland
 T +358 2 468 4600
 F +358 2 468 4601

Mirion Technologies (RADOS) GmbH
 Ruhrstrasse 49
 DE-22761 Hamburg
 Germany
 T +49 (0) 40 851 93-0
 F +49 (0) 40 851 93 256

www.mirion.com
 144215EN-B