

PDS-GO Personal Radiation Detector

The **PDS-GO** is a lightweight, small, sensitive, personal gamma radiation detector, designed to meet the ANSI N42.32 radiation detection requirements.

This instrument has been designed using the latest “state-of-the-art” electronic components including the advanced technology of Silicon photomultiplier as a detector.

The PDS-GO boasts a measuring range from background to 0.05 mSv/h (5 mR/h) with a sensitivity of 1,100 CPS/mR/h and is also ideal to use as a highly sensitive survey meter.

The instrument is especially useful for professionals dealing in safety and security of sensitive installations, public areas and border control. This small instrument (125 g) is easily carried on the body and is used to detect and indicate the presence and magnitude of gamma emitting radiation.



Highly Sensitive Survey Meter Featuring twin displays using two LCD's

On the top side, while it is carried on the user belt, with clear and simple indication of presence and intensity or absence of radiation field, and with an additional on front LCD with more and complementary information to the upper LCD, to be used after pulling out the instrument from belt.



FEATURES

- CsI(Tl) scintillation crystal for high efficiency to extended energy range
- Excellent sensitivity to ANSI source strength
- Excellent temperature stability
- Two operation modes (Detect/Search)
- Low power consumption – extended operating hours
- Instrument setup (alarm thresholds and other parameters) via USB connection to a PC using user-friendly software application.
- Record of event history
- Rechargeable battery – charging via USB connection inside the cradle
- Accessories include – protective silicon cover, belt clip, charging cradle, USB cable

Technical Specifications

Detector:	CsI(Tl) crystal with Silicon Photomultiplier
Measuring Range:	Background to 50 μ Sv/h (5 mR/h)
Energy Range:	60 KeV – 1.5 MeV
Sensitivity (¹³⁷Cs):	110 CPS/ μ Sv/h (1,100 CPS/mR/h)
Detection Capability:	0.5 μ Sv/h (50 μ R/h) above 0.25 μ Sv/h (25 μ R/h) background in less than 2 seconds
Time To Alarm:	<2 seconds
Alarm indication:	Adjustable: Visual, Vibration, Audible (1000–4000 Hz, 85 dB(A) at 30 cm)
Battery Life:	Li-ion 3.7V rechargeable battery, 120h power under normal conditions.
Operating temperature:	-20°C to + 50°C (Detection of ²⁴¹ Am in the whole temperature range)
Humidity:	Up to 93% at 35 °C
EMI	Meets ANSI 42.32
Protection Rating:	IP-64
Dimensions :	99mm x 55mm x 24mm (4" x 2" x 1")
Weight:	125 g with batteries
Communication:	via PC based user interface software (mini USB connection)



Accessories

Silicon Casing

Mini USB cable

Cradle, supplying power and communications enhances the instrument to become a highly sensitive fixed area monitor

Ordering No: BAK- 4061 (μ Sv/h)
BAK- 4060 (μ R/h)

ROTEM INDUSTRIES reserves the right to change specifications without advance notice

ROTEM INDUSTRIES LTD.
Radiation Detection Department
 Mishor Yamin, D.N. Arava 86800
 Tel. +972-8-6564781, Fax. +972-8-6573252
 E-mail. sales@rotemi.co.il Web: www.rotemi.co.il



ROTEM
 Rotem Industries Ltd

010802012